



KEY FEATURES

High-performance submeter GPS with integrated SBAS and EVEREST multipath technology

High-resolution VGA display for crisp and clear map viewing

Bluetooth and wireless LAN connectivity options

1 GB onboard storage plus SD slot for removable cards

Windows Mobile version 6 operating system

Rugged handheld with all-day battery



YOUR TOTAL GPS PLATFORM FOR FIELD DATA COLLECTION

The Trimble® GeoXT™ handheld, from the GeoExplorer® 2008 series, is the essential tool for maintaining your GIS. A high performance, submeter GPS receiver combined with a rugged handheld computer, the GeoXT handheld is ideal for use by utility companies, local government organizations, federal agencies, or anyone managing assets or mapping critical infrastructure who needs accurate data to do the job right—the first time.

Delivering consistent submeter accuracy both real-time and postprocessed, the GeoXT handheld is the most dependable submeter solution available. And it's specifically designed with your GIS in mind.

Real-world submeter performance

The GeoXT handheld is optimized to provide reliable location data when and where you need it. With advanced features like EVEREST™ multipath rejection technology, the GeoXT handheld records quality GPS positions even under canopy, in urban canyons, and in all the everyday environments you work in.

If you need submeter performance in real time, you can use WAAS, EGNOS, or MSAS corrections, or use the built-in Bluetooth® wireless technology to connect to a Trimble GeoBeacon™ receiver.

And if you need that extra edge in precision, you can collect data with Trimble TerraSync™ software or the Trimble GPScorrect™ extension for ESRI ArcPad software, and then postprocess it back in the office.

Packed full of power

With a powerful 520 MHz processor, 128 MB RAM, and 1 GB of onboard storage, the GeoXT handheld is a high performance device designed to work as hard as you do. The handheld gives you all the power you need to work with maps and large data sets in the field, and its high resolution VGA display allows for crisp and clear viewing of your data.

The GeoXT handheld is powered by the industry-standard Windows Mobile® version 6 operating system so you can choose a software solution designed for your field requirements, whether off-the-shelf or purpose-built.

The Windows Mobile 6 operating system includes familiar Microsoft® software, including Word Mobile, Excel Mobile, and Outlook® Mobile, giving you all the tools you need for a seamless exchange of data between the field and the office.

Built for the field

The GeoXT handheld has an integrated battery, good for a full day's work; simply charge the battery overnight and you're ready to go again. The GeoXT handheld will last the distance, and its rugged design can take a lot of punishment. Rain, hail or shine, it's built to keep working, whatever the weather throws at you.

Convenient connectivity

With the GeoXT handheld you have the flexibility to work exactly the way you want to. Do you need to access the Internet or your organization's secure network to get the most up-to-date data? No problem—with the GeoXT handheld you have built-in wireless LAN and Bluetooth technology to ensure you stay connected.

With Bluetooth wireless technology the GeoXT handheld also offers wireless connection to external devices such as Bluetooth-enabled laser rangefinders and barcode scanners for convenient cable-free solutions that keep you productive in the field.

Accuracy you can rely on

Accurate information is crucial to making informed decisions and improving the way you do business. The GeoXT handheld delivers consistent submeter accuracy both real-time and postprocessed, so you know your GIS has the information that others can depend on to do the job right—this time, next time and every time.

STANDARD FEATURES

System

- Windows Mobile 6 (Classic edition)
- VGA display (480 x 640), sunlight-readable color touchscreen
- Integrated Bluetooth 1.2 wireless technology
- Integrated 802.11b/g wireless LAN
- Ergonomic cable-free handheld
- Rugged and water-resistant design
- All-day internally rechargeable Li-ion battery
- Marvell 520 MHz XScale processor
- 128 MB RAM
- 1 GB non-volatile Flash data storage
- Sealed SD/SDHC card slot
- Integrated speaker and microphone

GPS

- Integrated high-performance GPS/SBAS¹ receiver and L1 antenna
- Submeter real-time or postprocessed accuracy
- RTCM and CMR real-time correction support
- TSIP and NMEA protocol support
- EVEREST multipath rejection technology

Standard Software

- GPS Controller for control of integrated GPS and in-field mission planning
- GPS Connector for connecting integrated GPS to external ports
- Microsoft Office Mobile
- Transcriber (handwriting recognition)

Standard Accessories

- Support module
- AC Power supply with International adapter kit
- USB data cable
- Stylus (x 2)
- Screen protectors (2-pack)
- Quick Start Guide
- Getting Started CD
- Hand strap
- Pouch

OPTIONAL FEATURES

Optional Software

- TerraSync software
- Trimble GPSCorrect extension for ESRI ArcPad software
- GPS Pathfinder[®] Tools Software Development Kit (SDK)
- GPS Pathfinder Office software
- Trimble GPS Analyst[™] extension for ESRI ArcGIS software
- TrimPix[™] software for wireless camera support. Download from www.trimble.com/trimpix.asp

Optional Accessories

- Power/serial clip (9-pin RS-232 serial connector and power input)
- Vehicle power adaptor²
- Li-ion external power kit²
- Null modem cable²
- Backpack kit
- Hard carry case
- Hurricane antenna kit
- External patch antenna
- Pole-mountable ground plane
- Baseball cap with patch antenna pocket
- 2 meter range pole
- Range pole bracket
- GeoBeacon receiver
- Anti-glare screen protectors (2-pack)

© 2008, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, GeoExplorer, and GPS Pathfinder are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. EVEREST, GPS Analyst, GPSCorrect, GeoBeacon, GeoXT, GPSCorrect, TerraSync, and TrimPix are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. Microsoft, Outlook, and Windows Mobile are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. PN 022501-164A (06/08)

TECHNICAL SPECIFICATIONS

Physical

Size 21.5 cm x 9.9 cm x 7.7 cm (8.5 in x 3.9 in x 3.0 in)
 Weight 0.80 kg (1.76 lbs) with battery
 Processor 520 MHz Marvell PXA-270 XScale processor
 Memory 128 MB RAM and 1 GB internal Flash storage
 Battery Internal 7500 mAh lithium-ion
 27.8 Watt-hours, rechargeable in unit

Power usage

Low (no GPS or backlight) 1.8 Watts
 Normal (with GPS and backlight³) 2.6 Watts
 High (with GPS, backlight³, Bluetooth, and wireless LAN)⁴ 3.7 Watts

Environmental

Operating temperature -20 °C to +60 °C (-4 °F to 140 °F)
 Storage temperature -30 °C to +70 °C (-22 °F to 158 °F)
 Casing Dust-proof and resistant to heavy wind-driven rain per IP 65 standard
 Slip-resistant grip, shock and vibration resistant
 Drop 0.9 m (3 ft) MIL-STD-810F, Method 516.5, Procedure IV

Input/Output

Expansion SD card slot (SD or SDHC storage cards)
 Display 8.9 cm (3.5 in) VGA (480 x 640 pixel) TFT, 16 bit (65,536) colors
 LED backlight
 Interface Touch screen, 10 hardware control keys, power status LED
 Audio system events, warnings, and notifications
 Soft Input Panel (SIP) virtual keyboard and handwriting recognition software
 Audio Microphone and speaker, record and playback utilities
 I/O USB 1.1 client via support module
 Serial via optional 9-pin RS-232 power/serial clip adaptor
 Radios⁵ Bluetooth 1.2, Wireless LAN 802.11b/g

GPS

Channels 14 (12 L1 code and carrier, 2 SBAS)
 Integrated real-time SBAS¹ (dual-channel tracking)
 Update rate 1 Hz
 Time to first fix 30 seconds (typical)
 Protocols
 Data output TSIP, NMEA-0183 v3.0 (GGA, VTG, GLL, GSA, GSV, RMC)
 Real-time corrections RTCM 2.x, RTCM 3.0, CMR, CMR+

Accuracy (HRMS)⁶ after differential correction

Postprocessed Submeter
 Real-time (SBAS¹ or external correction source) Submeter

- 1 SBAS (Satellite Based Augmentation System). Includes WAAS available in North America only, EGNOS available in Europe only, and MSAS available in Japan only.
- 2 Power/serial clip also required.
- 3 With backlight at default setting (50% brightness).
- 4 Power draw will vary depending on radio usage.
- 5 Bluetooth and wireless LAN type approvals are country specific. GeoExplorer 2008 series handhelds have Bluetooth and wireless LAN approval in the U.S. and in most European countries. For further information please consult your local reseller.
- 6 Horizontal Root Mean Squared accuracy, 1-sigma (63%). Requires data to be collected with minimum of 5 satellites, maximum PDOP of 6, minimum SNR of 39 dBHz, minimum elevation of 15 degrees, and reasonable multipath conditions. Ionospheric disturbances, multipath signals or obstruction of the sky by buildings or tree canopy may degrade precision by interfering with signal reception. Except when using VRS corrections, accuracy varies with proximity to base station by +1 ppm for postprocessing and real-time.

Specifications subject to change without notice.



NORTH & SOUTH AMERICA

Trimble Navigation Limited
 10355 Westmoor Drive
 Suite #100
 Westminster, CO 80021
 USA
 +1-720-587-4574 Phone
 +1-720-587-4878 Fax

EUROPE & AFRICA

Trimble GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY
 +49-6142-2100-0 Phone
 +49-6142-2100-550 Fax

ASIA-PACIFIC & MIDDLE EAST

Trimble Navigation
 Singapore PTE Limited
 80 Marine Parade Road
 #22-06 Parkway Parade
 Singapore, 449269
 SINGAPORE
 +65-6348-2212 Phone
 +65-6348-2232 Fax

YOUR LOCAL TRIMBLE OFFICE OR REPRESENTATIVE



www.trimble.com
store.trimble.com